

# FREE WEIGHT AREAS



TECHNICAL DATA SHEET

**PAVIGYM**  
THE BASIS OF FITNESS

## **P** PAVIGYM ENDURANCE S&S

Extra-thickness for more protection  
against impacts for heavy loads.

Unique aesthetics for free weight & power lifting areas where increased sound and vibration absorption is essential.


# TECHNICAL INFORMATION

Weight		16 kg
Density	UNE-53526	900 kg/m <sup>3</sup>
Hardness	din 53505	75° Shore A
% water absorption	ASTM D570	0%
Coef. linear dilatation	0°C-40°C	10 <sup>-4</sup> °C <sup>-1</sup>
Fire classification	EN 13501-1	Cfl-s1
Formaldehyde emission	EN 717-2	<0,5
Sound insulation	ISO 10140-3	21 dB


# COMPARATIVE CHART

	PAVIGYM ENDURANCE S&S	PAVIGYM ENDURANCE	RECYCLED RUBBER (ROLLS)
Comfort	*****	***	**
Marks resistance (medium loads)	*****	****	***
Marks resistance (heavy loads)	****	***	**
Sound insulation	*****	***	**
Durability	*****	****	***
Hygienic / Anti-bacterial protection	*****	*****	**
Thermal insulation	*****	*****	***
Water resistance	*****	*****	***
Easy to install & maintain	*****	*****	**


# COLOURS




PAVIGYM WENGUE




PAVIGYM BEECHWOOD



PAVIGYM STONE GREY



PAVIGYM B. MARBLE\*  
\*GRAINED EFFECT



PAVIGYM JET BLACK

## SPECIAL COLOURS

\*Contact us for more info about availability.



PAVIGYM CYAN



PAVIGYM LIME



PAVIGYM RED




PAVIGYM WALNUT

The appearance and color of these pictures may differ slightly from the final product.



INTERLOCKING SYSTEM



THICKNESS  
22 MM



**Top Layer**

Virgin rubber= resistance and friction

**Bottom Layer**

Rubber + air = Impact absorption + sound absorption



TOP LAYER VIRGIN RUBBER

# FREE WEIGHT AREAS

**P**AVIGYM  
ENDURANCE S&S

