

# FREE WEIGHT AREAS



TECHNICAL DATA SHEET

## **P** PAVIGYM EXTREME S&S

Specifically designed for heavy duty & weight training areas where maximum level of resistance and sound absorption is needed.

# TECHNICAL INFORMATION

		90x90cm
Weight		15,5 kg
Density	UNE-53526	900 kg/m <sup>3</sup>
% water absorption	ASTM D570	0%
Coef. linear dilatation	0°C-40°C	10 <sup>-40</sup> C <sup>-1</sup>
Fire classification	EN 13501-1	Efl
Sound insulation	ISO 10140-3	20 dB

# COMPARATIVE CHART

	PAVIGYM EXTREME S&S	PAVIGYM EXTREME	RECYCLED RUBBER (ROLLS)
Comfort	*****	***	**
Marks resistance (regular loads)	*****	*****	*****
Marks resistance (big loads)	*****	***	**
Sound insulation	*****	***	***
Durability	****	*****	***
Hygienic / Anti-bacterial protection	***	*****	***
Thermal insulation	*****	***	***
Water resistance	*****	*****	***
Easy to install & maintain	****	*****	**

# COLOURS

\*The appearance and color of these pictures may differ slightly from the final product.



PAVIGYM  
PURE STONE



PAVIGYM  
VULCANO BLACK




PAVIGYM  
NATURAL CLAY



PAVIGYM  
BROWN GRAVEL

# SPECIAL COLOURS




PAVIGYM LTD CYAN



PAVIGYM LTD ORANGE



PAVIGYM LTD GREEN



PAVIGYM LTD YELLOW




PAVIGYM BLACK & BLACK

\*Contact us for more details about availability.



INTERLOCKING SYSTEM



THICKNESS  
22 MM



**Top Layer**  
Virgin rubber= resistance and friction

**Bottom Layer**  
Rubber + air = Impact absorption + sound absorption



TOP LAYER:  
VIRGIN RUBBER



# FREE WEIGHT AREAS

**P** PAVIGYM  
EXTREME S&S

