



DATASHEET

PAVIGYM
THE BASIS OF FITNESS

PAVIGYM
FUNCTIONAL

A functional flooring for a functional workout

Designed to offer shock absorption while improving stability. Comfortable and smooth, this floor is resistant to functional equipment shocks, and it does not get marked.

TECHNICAL INFO

Net size		90x90 cm
Thickness		20 mm
Weight		6,3 Kg
Hardness	UNE 53130	60 °ShA
Average density	UNE 53526	0.385 g/ cm ³
Friction		≥ 0.6
Abrasion resistance	UNE 53527 (10N)	180 mm ³
Contraction	24 h;70°C	0,1%

COMPARATIVE CHART

	PAVIGYM FUNCTIONAL	RECYCLED RUBBER	WOODEN SPRING	LINOLEUM (PVC)
Comfort and wellness	*****	**	***	***
Shock absorption	*****	**	**	****
Movement protection (Slip/blocking)	*****	**	***	***
Sound insulation	*****	***	**	***
Thermal insulation	*****	**	****	****
Durability	*****	****	***	**
Water resistance	*****	***	**	****
Easiness and short installation time	*****	****	**	***
Damaged area replacement (modularity)	*****	**	*	*



COLOURS

PAVIGYM **WENGUE**PAVIGYM **BEECHWOOD**PAVIGYM **STONE GREY**PAVIGYM **B. MARBLE**

**The appearance and color of these pictures may differ slightly from the final product.*



INTERLOCKING SYSTEM



5 mm Top Layer
Virgin rubber + Pavigym friction compounds = Resistance + Optimized friction

15 mm Bottom Layer
Micro-cellular polyurethane = Impact absorption + elastic module

